

Diagram of a cantilever beam fixed to a wall on the left and free on the right. The beam has a total length L . A coordinate system is shown at the fixed end with x pointing right and y pointing down. A unit load P is applied downwards at the free end. The beam is divided into segments with varying cross-sections, labeled 1, 2, 3, and 4. A break symbol is shown in the middle of the beam.

Notes

- 1. RoHS & Pb-FREE**
- 2. CONNECTOR FINISHES**
- 2-1. TNC PS--- ▶▶ BODY : Nickel Plating
CONTACT : Gold Plating
CAP : Nickel Plating**
- 2-2. SMA PS--- ▶▶ BODY : Nickel Plating
CONTACT : Gold Plating
COUPLING CAP : Nickel Plating**



4	BONDING TUBE	2	LS TUBE	ATU00350-N/1	Ø7_Black
3	CONNECTOR	1	KJ COMTECH	CN00958-7/2	SMA50 PS
2	CONNECTOR	1	KJ COMTECH	CN02192-7/2	TNC50 PS
1	COAXIAL CABLE	1	COAXPARK	ACA00058-N/1	LMR240(50Ω)
NO.	DESCRIPTION	Q'TY	VENDER	PART NO.	RAMARKS
DATE 2017. 06. 30.			 KJ COMTECH CO.,LTD. RF & MICROWAVE TECHNOLOGY Tel : 02-02-047-0016 Fax : 02-02-047-0017		
APPROVED BY	I.C.KIM	TITLE CABLE ASSEMBLY			
CHECKED BY					
DRAWN BY	S.Y.EUN				
CHECKED BY		A4 DWG NO. CF00401-7/1 DETAIL NO. REVISION I R SHEET 1 of 1			
SCALE	UNIT				
N/S	mm				
					