

CF00537-7/1



SMA-PS+SMA-PS

+141FJ(BLUE)

SMA PS 141TP

BO/GO, PI/GO, CH/BR/NI

FERRULE-X, BONDING TUBE

CF00537-7/1 152mm

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40°C ~ 125°C

152mm - S11/S22/S21
(SWR, SWR, dB)

■_1.0GHz	- 1.02, 1.02, 0.12
■_2.0GHz	- 1.09, 1.09, 0.20
■_3.0GHz	- 1.02, 1.02, 0.23
■_4.0GHz	- 1.04, 1.04, 0.27
■_5.0GHz	- 1.07, 1.08, 0.31
■_6.0GHz	- 1.14, 1.14, 0.32
■_7.0GHz	- 1.28, 1.30, 0.46
■_8.0GHz	- 1.11, 1.14, 0.41

► NETWORK ANALYZER

► Test cable

► Test Adaptor

■ E5071B (~8.5GHz)

■ N Male to SMA Male

□ ZVA50 (~50GHz)

10GHz Cable (CF00540-7/1)

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

