

CF00547-7/2



**SMA-PS+SMA-PS
+RG316(BROWN)**

SMA PS RG316

BO/GO, PI/GO, CH/BR/NI

CF00547-7/2 100mm

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40°C ~ 125°C

**100mm - S11/S22/S21
(SWR, SWR, dB)**

■_0.5GHz	- 1.01, 1.00, 3.11
■_1.0GHz	- 1.03, 1.02, 4.59
■_1.5GHz	- 1.03, 1.01, 5.82
■_2.0GHz	- 1.04, 1.01, 6.92
■_3.0GHz	- 1.03, 1.03, 8.82
■_4.0GHz	- 1.06, 1.04, 10.47
■_5.0GHz	- 1.09, 1.12, 11.98
■_6.0GHz	- 1.14, 1.17, 13.42

► **NETWORK ANALYZER**

► **Test cable**

► **Test Adaptor**

■ E5071B (~8.5GHz)

■ N Male to SMA Male

■ SMA (J) SMA (J) ST

□ ZVA50 (~50GHz)

10GHz Cable (CF00540-7/1)

AD00006-7/2

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

