

CF00655-7/1



**N-PS+SMA-PS  
+141FJ(BLUE)**

N PS 141TP

BO/SU, PI/SI, CH/BR/SU

SMA PS 141TP

BO/GO, PI/GO, CH/BR/NI

**CF00655-7/1 203mm**

|                |               |
|----------------|---------------|
| Frequency      |               |
| Insertion Loss |               |
| VSWR           |               |
| Impedance      | ■ 50Ω □ 75Ω   |
| Temperature    | -40°C ~ 125°C |

**203mm- S11/S22/S21  
(SWR, SWR, dB)**

|          |                    |
|----------|--------------------|
| ■_1.0GHz | - 1.07, 1.07, 0.08 |
| ■_2.0GHz | - 1.08, 1.08, 0.14 |
| ■_3.0GHz | - 1.02, 1.01, 0.18 |
| ■_4.0GHz | - 1.05, 1.05, 0.22 |
| ■_5.0GHz | - 1.08, 1.08, 0.26 |
| ■_6.0GHz | - 1.04, 1.06, 0.29 |
| -----    |                    |
| ■_7.0GHz | - 1.06, 1.05, 0.36 |
| ■_8.0GHz | - 1.16, 1.06, 0.50 |

► **NETWORK ANALYZER**

► **Test cable**

► **Test Adaptor**

■ E5071B (~8.5GHz)

■ N Male to SMA Male

■ SMA (J) SMA (J) ST

□ ZVA50 (~50GHz)

10GHz Cable (CF00540-7/1)

AD00006-7/2

■ N (J) SMA (J) AD00424-7/1

TR1 : IN PORT VSWR(S11), TR2 : OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

