

CF00859-7/1



TNC-PS+TNC-PS
+LMR400-UF(TIMES)
TNC PS LMR400
BO/NI, PI/GO, CH/BR/NI

CF00859-7/1 10M

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40°C ~ 125°C

10M
S11/S22/S21
(SWR, SWR, dB)

■_1.0GHz	- 1.03, 1.04, 1.62
■_2.0GHz	- 1.07, 1.06, 2.43
■_3.0GHz	- 1.06, 1.05, 3.08

■_4.0GHz	- 1.06, 1.26, 3.77
■_5.0GHz	- 1.29, 1.25, 4.26
■_6.0GHz	- 1.29, 1.20, 4.74
■_7.0GHz	- 1.14, 1.09, 5.03

► **NETWORK ANALYZER**

► **Test cable**

► **Test Adaptor**

■ E5071B (~8.5GHz)

■ N Male to SMA Male

■ SMA (J) TNC (J) PE사

□ ZVA50 (~50GHz)

10GHz Cable (CF00540-7/1)

TR1 : IN PORT VSWR(S11), TR2 : OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

