

CF00863-7/1

CF00863-7/1 127mm 6G

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40°C ~ 125°C

127mm
S11/S22/S21
(SWR, SWR, dB)

■_0.5GHz	- 1.01, 1.01, 0.13
■_1.0GHz	- 1.09, 1.10, 0.21
■_1.5GHz	- 1.13, 1.12, 0.29
■_2.0GHz	- 1.06, 1.07, 0.31
■_3.0GHz	- 1.12, 1.08, 0.43
■_4.0GHz	- 1.19, 1.20, 0.60
■_5.0GHz	- 1.33, 1.54, 2.32
■_6.0GHz	- 1.47, 1.39, 1.17
■_Max/	- 2.07, 1.75, 3.76

MMCX-PL+SMA-PL
+RG316(BROWN)

MMCX PL RG316 V:8

BO/Go PI/Go

SMA PL RG316

BO/GO, PI/GO, CH/BR/NI

► NETWORK ANALYZER

► Test cable

► Test Adaptor

□ E5071B (~8.5GHz)

■ N Male to SMA Male

■ SMA (J) SMA (J) ST

■ ZVA50 (~50GHz)

10GHz Cable (CF00540-7/1)

AD00006-7/2

■ MMCX (J) SMA (J) ST

AD00368-7/1

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

