

CF00894-7/1



**SMA-PL+SMA-PS
+RG316(BROWN)**
SMA PL RG316
BO/GO, PI/GO, CH/BR/NI
SMA PS RG316
BO/GO, PI/GO, CH/BR/NI

CF00894-7/1 102mm 6G

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40°C ~ 125°C

**102mm
S11/S22/S21
(SWR, SWR, dB)**

■_0.5GHz	- 1.03, 1.03, 0.11
■_1.0GHz	- 1.05, 1.05, 0.15
■_1.5GHz	- 1.06, 1.07, 0.18
■_2.0GHz	- 1.06, 1.07, 0.22
■_3.0GHz	- 1.03, 1.05, 0.28
■_4.0GHz	- 1.15, 1.13, 0.33
■_5.0GHz	- 1.18, 1.18, 0.39

■_6.0GHz	- 1.20, 1.23, 0.46
■_MaX/	- 1.20, 1.23, 0.45

► **NETWORK ANALYZER**

► **Test cable**

► **Test Adaptor**

□ E5071B (~8.5GHz)

■ N Male to SMA Male

■ SMA (J) SMA (J) ST

■ ZVA50 (~50GHz)

10GHz Cable (CF00540-7/1)

AD00006-7/2

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

