



**SMA-PL+SMBL-PL
+SIFS(BLACK)**

SMA PL SIFS

BO/GO, PI/GO, CH/BR/NI

SMBL PL SIFS V:16.3 CAPΦ9

BO/NI, PI/GO, CC/BR/NI

CF00952-7/1 185mm

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40°C ~ 125°C

S11/S22/S21 (SWR, SWR, dB)

■_1.0GHz	- 1.04, 1.05, 0.50
■_2.0GHz	- 1.07, 1.05, 0.76
■_3.0GHz	- 1.07, 1.06, 0.94
■_4.0GHz	- 1.03, 1.05, 1.11

■_5.0GHz	- 1.22, 1.23, 1.29
■_6.0GHz	- 1.08, 1.23, 1.38
■_7.0GHz	- 1.19, 1.24, 1.54
■_8.0GHz	- 1.30, 1.34, 1.72

► NETWORK ANALYZER

► Test cable

► Test Adaptor

■ E5071B (~8.5GHz)

■ N Male to SMA Male

■ SMA (J) SMA (J) ST
AD00006-7/2

□ ZVA50 (~50GHz)

10GHz Cable (CF00540-7/1)

■ SMA (J) SMLB (J) ST
AD00515-7/1

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

