

CF01044-7/2



**SMA-PS+SMBL-JS
+EM-1.5D-HQEW**

SMA PS 1.5D

BO/GO, PI/GO, CH/BR/NI

SMBL JS EM-1.5D

BO/NI, PI/GO

CF01044-7/2 2.5M

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40°C ~ 125°C

**2.5M - S11/S22/S21
(SWR, SWR, dB)**

■ _1.0GHz	- 1.03, 1.01, 2.17
■ _1.5GHz	- 1.09, 1.09, 2.77
■ _2.0GHz	- 1.08, 1.08, 3.26
■ _2.5GHz	- 1.06, 1.07, 3.71
■ _3.0GHz	- 1.05, 1.06, 4.14
■ _4.0GHz	- 1.20, 1.11, 4.98

■ _5.0GHz	- 1.22, 1.09, 5.78
■ _6.0GHz	- 1.47, 1.36, 6.70

► **NETWORK ANALYZER**

► **Test cable**

► **Test Adaptor**

■ E5071B (~8.5GHz)

■ N Male to SMA Male

■ SMA (J) SMA (J) ST
AD00006-7/2

□ ZVA50 (~50GHz)

10GHz Cable (CF00540-7/1)

■ SMA (J) SMLB (P) ST
AD00491-7/4

TR1 : IN PORT VSWR(S11), TR2 : OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

