

CF01074-7/1



N-JS+N-PS

+RG142

N JS RG400 BO/NI, PI/GO

N PS RG400

BO/NI, PI/GO, CH/BR/NI

CF01074-7/1 2.4M

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40°C ~ 125°C

2.4M - S11/S22/S21 (SWR, SWR, dB)

■_1.0GHz	- 1.08, 1.06, 1.17
■_2.0GHz	- 1.20, 1.12, 1.75

■_3.0GHz	- 1.43, 1.21, 2.30
■_4.0GHz	- 1.76, 1.38, 2.89
■_5.0GHz	- 1.93, 1.42, 3.35
■_6.0GHz	- 1.76, 1.17, 3.59
■_7.0GHz	- 2.07, 1.58, 4.13
■_8.0GHz	- 2.21, 1.36, 4.55

▶ NETWORK ANALYZER

▶ Test cable

▶ Test Adaptor

■ E5071B (~8.5GHz)

■ N Male to N Male

■ N (J) N (J) AD00379-7/2

□ ZVA50 (~50GHz)

10GHz Cable (CF00539-7/1)

TR1 : IN PORT VSWR(S11), TR2 : OUT PORT VSWR(S22), TR3 : Insertion Loss (S21)

