

CF01465-7/1

CF01465-7/1 417mm

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40°C ~ 125°C

417mm Both assy - S11/S22/S21 (SWR, SWR, dB)

■_1.0GHz	- 1.02, 1.02, 0.34
■_2.0GHz	- 1.02, 1.02, 0.51
■_3.0GHz	- 1.01, 1.01, 0.63
■_4.0GHz	- 1.03, 1.02, 0.75
■_5.0GHz	- 1.02, 1.02, 0.84
■_6.0GHz	- 1.01, 1.02, 0.93
■_7.0GHz	- 1.04, 1.04, 1.03
■_8.0GHz	- 1.07, 1.07, 1.13

SMA-PS+OPEN+85TP
SMA PS 85F Solder
BO/Go PI/Go CAP/BR/NI

► NETWORK ANALYZER

► Test cable

► Test Adaptor

■ E5071B (~8.5GHz)

■ N Male to SMA Male

■ SMA (J) SMA (J) ST

□ ZVA50 (~50GHz)

10GHz Cable (CF00540-7/1)

AD00006-7/2

TR1 : IN PORT VSWR(S11), TR2 : OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

