



N-PS+SMA-PS
+EM-1.5D-HQEW
N PS 1.5D-HQEW Crimp
BO/Ni PI/Go CAP/BR/NI
SMA PS 1.5D-HQEW Crimp
BO/Go PI/Go CAP/BR/NI

CF01518-7/1 2.5M	
Frequency	
Insertion Loss	
VSWR	
Impedance	☒ 50Ω ☐ 75Ω
Temperature	-40℃ ~ 125℃

2.5M - S11/S22/S21 (SWR, SWR, dB)	
☒ _0.5GHz	- 1.05, 1.04, 1.51
☒ _1.0GHz	- 1.03, 1.03, 2.19
☒ _1.5GHz	- 1.08, 1.07, 2.74
☒ _2.0GHz	- 1.15, 1.12, 3.25
☒ _3.0GHz	- 1.11, 1.13, 4.12
☒ _4.0GHz	- 1.02, 1.20, 4.95

☒ _5.0GHz	- 1.04, 1.23, 5.79
☒ _6.0GHz	- 1.11, 1.15, 6.66

▶ **NETWORK ANALYZER** ▶ **Test cable** ▶ **Test Adaptor**

- ☐ E5071B (~8.5GHz)
- ☒ N Male to SMA Male
- ☐ ZVA50 (~50GHz)
- 10GHz Cable (CF00540-7/1)
- ☒ ZND (~8.5GHz)

TR1 : IN PORT VSWR(S11), TR2 : OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

