

CF01685-7/1

TWO BODY  
JACK/BE.CU

ONE\_BODY  
BRASS

CF01685-7/1 115mm

|             |                                                                      |
|-------------|----------------------------------------------------------------------|
| S11         |                                                                      |
| S22         |                                                                      |
| S21         |                                                                      |
| Impedance   | <input checked="" type="checkbox"/> 50Ω <input type="checkbox"/> 75Ω |
| Temperature | -40℃ ~ 125℃                                                          |

|        |   |      |      |      |
|--------|---|------|------|------|
| 1.0GHz | - | 1.08 | 1.08 | 0.15 |
| 2.0GHz | - | 1.10 | 1.10 | 0.26 |
| 3.0GHz | - | 1.08 | 1.09 | 0.34 |
| 4.0GHz | - | 1.08 | 1.08 | 0.42 |
| 5.0GHz | - | 1.12 | 1.12 | 0.49 |
| 6.0GHz | - | 1.16 | 1.15 | 0.54 |
| 7.0GHz | - | 1.20 | 1.19 | 0.57 |
| 8.0GHz | - | 1.23 | 1.21 | 0.57 |

---

|                 |        |
|-----------------|--------|
| VSWR MAX 7.0GHZ | 1.23:1 |
|-----------------|--------|

MCX-PL+MCX-PS +47F  
MCX PL 47TP V:8.6mm  
BO/GO, PI/GO  
MCX PS 47TP BO/GO, PI/GO

► NETWORK ANALYZER    ► Test cable    ► Test Adaptor

- ☐ E5071B (~8.5GHz)  
☒ ZND (~8.5GHz)  
☐ ZVA50 (~50GHz)
- ☒ N Male to SMA Male  
10GHz Cable (CF00540-7/1)  
☐ N Male to N Male  
10GHz Cable (CF00539-7/1)  
☐ 2.4mm Male to 2.4mm Male  
50GHz Cable

TR1 : IN PORT VSWR(S11), TR2 : OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

