

REVISION				
REV	DESCRIPTION	DRAWN	APPR	DATE
IR	Initial Registration	S.Y.EUN	S.H.KIM	2022.01.11.

*ELECTRICAL


Impedance : 50 Ohm
Freq. Range : DC to 6 GHz
VSWR : 1.22:1
Working Voltage :500 Vrms @Sea level
Dielectric Withstand Voltage : 1500Vrms
Insulation Resistance :5000 MOhms Min
Contact Resistance (center):2.0 mohm
(outer):3.0 mohm

*MECHANICAL

Interface Dimensions : MIL-STD-348
Force to Engage and Disengage : N/A
Coupling Nut Retention Force and Proof Torque N/A
Connector Durability : 500 mating cycles min.

*ENVIRONMENTAL

Temp. Range : -65°C to +125°C
Thermal Shock : MIL-STD-202, Method 107, Test Cond. B
Vibration : MIL-STD-202, Method 204, Test Cond. D
Shock : MIL-STD-202, Method 213, Test Cond. I



5	SHRINK TUBE	1	—	BLACK	ATU00056-N/1(ø4-12mm)
4	GASKET	1	SILICONE	RED	DGK00028-N/1
3	INSULATOR	1	TEFLON		DIN02547-N/2
2	CONTACT	1	BeCu C17300	Gold Plate	DCT03413-5/5
1	BODY	1	MBsBD C3604BD-F	Nickel Plate	DBD03881-5/4
NO.	DESCRIPTION	Q'TY	MATERIAL	PLATING	CODE

TOLERANCE	Decimal	DATE 2022. 01. 11.		 RF & MICROWAVE TECHNOLOGY Tel : 82-32-347-8015 Fax : 82-32-347-8017
	Angle	APPROVED BY	S.H.KIM	
MATERIAL		CHECKED BY		KJ COMTECH CO.,LTD. TITLE TNC50 SOLDER END JS-4H
		DRAWN BY	S.Y.EUN	
FINISH		SCALE	3/1	DWG NO. CN03385-7/6 REVISION I R SHEET 1 of 1
		UNIT	mm	

A4