




* 삽이탈력 확인 (AD00568-7/1) - 상대물 체결


-삽입력 : 1.0Kgf~1.2Kgf

-이탈력 : 0.4Kgf~0.6Kgf



CABLE 탈피도

*플랜지 2H 좌측커팅



5	COVER	1	MBsBD C3604BD-F	Nickel Plate	DCO00020-5/2
4	INSULATOR	1	TEFLON		DIN00921-N/1
3	INSULATOR	1	TEFLON		DIN03048-N1
2	CONTACT	1	MBsBD C3604BD-F	Gold Plate	DCT03534-5/4
1	1-2 BODY	1	MBsBD C3604BD-F	Nickel Plate	DBB00420-3/9
	1-1 BODY	1	SUS	Nickel Plate	DBD03906-5/7 DBD03985-5/8
NO.	DESCRIPTION	Q'TY	MATERIAL	PLATING	CODE

TOLERANCE	Decimal	DATE 2019. 05. 20.		 RF & MICROWAVE TECHNOLOGY Tel : 82-32-347-8015 Fax : 82-32-347-8017
	Angle	APPROVED BY	I.C.KIM	
MATERIAL		CHECKED BY		KJ COMTECH CO.,LTD. TITLE GIGA LANE(1.2t) CABLE JL-2H RF-ø1.37
		DRAWN BY	S.Y.EUN	
FINISH		SCALE	4/1	DWG NO. CN03457-7/8 REVISION I R SHEET 1 of 1
		UNIT	mm	