


REVISION				
REV	DESCRIPTION	DRAWN	APPR	DATE
1A	Initial Registration	S.Y.EUN	I.C.KIM	2019.05.17.
1	특성개선으로 인한 PIN 변경	S.Y.EUN	I.C.KIM	2020.07.23.




ELECTRICAL DATA


1. IMPEDANCE : 50ohm
2. FREQUENCY RANGE : DC~40GHz
3. VSWR (Max) : 1.2

Mate compatible table	
SMA [~18GHz]	Mate
3.5mm [~26.5GHz]	
2.92mm(K) [~40GHz]	
2.4mm [~50GHz]	Mate
1.85mm(V) [~65GHz]	

Un mate



8	CLAMP	1	MBsBD C3604BD-F	Nickel Plate	DBN00212-5/5
7	CAP	1	SUS	Passivated	DCU00006-5/1
6	SPRING RING	1	SUS304	부동태 처리	DSR00002-5/1
5	INSERT	1	MBsBD C3604BD-F	Gold Plate	DIS00282-5/2
4	INSERT	1	SUS	Passivated	DIS00281-5/5
3	INSULATOR	1	PEEK		DIN02942-N/C
2	CONTACT	1	BeCu C17300	Gold Plate 1.3μm	DCT03945-5/4 DCT03945-5/5
1	BODY	1	SUS	Passivated	DBD04399-5/5
NO.	DESCRIPTION	Q'TY	MATERIAL	PLATING	CODE

TOLERANCE	Decimal ±0.2	DATE 2020. 07. 23.			 RF & MICROWAVE TECHNOLOGY Tel : 82-32-347-8015 Fax : 82-32-347-8017
	Angle ±1°	APPROVED BY I.C.KIM			
MATERIAL _____	CHECKED BY		TITLE SMA 2.92mm CABLE PS MUA165SD DJ		
	DRAWN BY S.Y.EUN				
FINISH _____	SCALE 5/1	UNIT mm		A4	DWG NO. CN03779-7/7
					REVISION 1