

Mate compatible table	
SMA [~18GHz]	Mate
3.5mm [~26.5GHz]	
2.92mm(K) [~40GHz]	
2.4mm [~50GHz]	Mate
1.85mm(V) [~65GHz]	

Un mate

ELECTRICAL DATA

1. IMPEDANCE : 50ohm
2. FREQUENCY RANGE : DC~40GHz
3. VSWR (Max) : 1.2

REVISION				
REV	DESCRIPTION	DRAWN	APPR	DATE
IR	Initial Registration	S.H.KIM		2022.07.14.

1/4-36 UNS-2A

0.1±0.01

※동심도 편차 필히 검사 할 것

◎ Max0.2 A

ø0.64±0.03

7.8

(1.6)

※6.94±0.1

16.34

2-ø2.6 thru

4-C1.75

ø4.50±0.03

12.20

ø16.0

5.6

3	INSULATOR	1	TEFLON		DIN02928-N/1
2	CONTACT	1	BeCu C17300	Gold Plate	DCT03864-5/1
1	BODY	1	SUS	Gold Plate	DBD04488-5/2
NO.	DESCRIPTION	Q'TY	MATERIAL	PLATING	CODE

TOLERANCE	Decimal ±0.2	DATE 2022. 07. 14.			 RF & MICROWAVE TECHNOLOGY Tel : 82-32-347-8015 Fax : 82-32-347-8017		
	Angle ±1°	APPROVED BY					
	MATERIAL _____		CHECKED BY			TITLE 2.92mm SOLDER END JS-2H	
FINISH _____		DRAWN BY	S.H.KIM				
		SCALE 4/1	UNIT mm		A4	DWG NO. CN03833-7/2	
						REVISION	I R