



REVISION		
REV	DESCRIPTION	DATE
IR	Initial Registration	2010.01.04.



* ELECTRICAL SPECIFICATIONS
Frequency Range : 1800.0 ~ 2200.0MHz
Coupling Value : 20.0 $\pm$ 0.5dB / 30.0 $\pm$ 0.5dB
Insertion Loss (Max.) : 0.3dB
V.S.W.R (Max.) : 1.2 : 1
Directivity (Min.) : 20.0dB
Impedance : 50.0 Ω

* MECHANICAL SPECIFICATIONS
HOUSING : A6061 T6 (White Chromate)
CONNECTORS : MBsBD (Nickel Plate)
CONNECTORS PINS : Beryllium Copper (Gold Plate)
INSULATORS : TEFLON

TOLERANCE	Decimal	DATE 2010. 01. 04.		 RF & MICROWAVE TECHNOLOGY Tel : 82-32-347-8015 Fax : 82-32-347-8017
	Angle	APPROVED BY	J.H.YOUN	
MATERIAL	A6061 T6	CHECKED BY		KJ COMTECH CO.,LTD. TITLE 20/30dB Dual Coupler
		DRAWN BY	K.I.CHO	
FINISH	White Chromate	SCALE	1/1	A4 DWG NO. DC00201-7/1 REVISION I R SHEET 1 of 1
		UNIT	mm	