


REVISION				
REV	DESCRIPTION	DRAWN	APPR	DATE
1	Initial Registration	T.J.KIM	J.H.YOUN	2015.10.15.



* ELECTRICAL SPECIFICATIONS
Frequency Range : 600~3600MHz
Insertion Loss (Max.) : 0.5dB
Input V.S.W.R (Max.) : 1.2 : 1
Coupling Value : 10 ± 1dB
Directivity (Min.) : 20dB
Power Handling (Max.) : 200.0W
PIMD (Max.) : -150dBc (@ 43dB 2 tone)
Impedance : 50Ω

* MECHANICAL SPECIFICATIONS
HOUSING : A6061 (DIC-582)
CONNECTORS : MBsBD (SUCO Plate)
CONNECTORS PINS : Beryllium Copper (Silver Plate)
INSULATORS : TEFLON

* ENVIRONMENTAL SPECIFICATION
IP-67

TOLERANCE	Decimal ±0.3	DATE	2015. 10. 15.	 KJ COMTECH CO., LTD. RF & MICROWAVE TECHNOLOGY Tel : 82-32-347-8015 Fax : 82-32-347-8017
	Angle ±1°	APPROVED BY	J.H.YOUN	
MATERIAL	A6061 T6	CHECKED BY	S.L.SON	TITLE 10dB DIRECTIONAL COUPLER
		DRAWN BY	T.J.KIM	
FINISH	DIC-582(BLACK)	SCALE	1/1	A3 DWG NO. DC00321-6/1 REVISION 1 SHEET 1 of 1
		UNIT	mm	