


REVISION				
REV	DESCRIPTION	DRAWN	APPR	DATE
1	Initial Registration	K.S.KIM	S.L.SON	2022.11.16.



* ELECTRICAL SPECIFICATIONS

Parameter	Unit	Specification			Comments
Frequency	MHz	DC~120	150~200	240~2000	
In/Out VSWR	dB	-	1.5:1	-	Max.
Insertion Loss	dB	-	1.5	-	Max.
Flatness	dB	-	1	-	Max.
Rejection	dB	20	-	30	Min.
Handling Power	W	1			Max.
Impedance	Ω	50			

* MECHANICAL SPECIFICATIONS

HOUSING : A6061 (White Chromate)

CONNECTORS : MBsBD (Nickel Plate)

CONNECTORS PINS : MBsBD (Gold Plate)

INSULATORS : TEFLON

* ENVIRONMENTAL SPECIFICATION

-20°C ~ 70°C

TOLERANCE	Decimal ±0.3	DATE	2022. 11. 16.	 RF & MICROWAVE TECHNOLOGY Tel : 82-32-347-8015 Fax : 82-32-347-8017
	Angle ±1°	APPROVED BY	S.L.SON	
MATERIAL	A6061 T6	CHECKED BY	S.L.SON	TITLE Band Pass Filter
		DRAWN BY	K.S.KIM	
FINISH	White Chromate	SCALE	1/1	UNIT mm
		A3		DWG NO. FT00772-7/1
		REVISION 1		SHEET 1 of 1