



REVISION				
REV	DESCRIPTION	DRAWN	APPR	DATE
1	Initial Registration	K.S.KIM	S.L.SON	2022.03.04.



5-SMA FEMALE



* ELECTRICAL SPECIFICATIONS
Frequency Range : 2000 ~ 8000MHz
Insertion Loss (Max.) : 7.8dB
V.S.W.R (Max.) : 1.4 : 1
Isolation (Min.) : 18.0dB
Power Handling (Max.) : 1.0W
Impedance : 50.0 Ω

* MECHANICAL SPECIFICATIONS
HOUSING : A6061 T6 (White Chromate)
CONNECTORS : MBsBD (Nickel Plate)
CONNECTORS PINS :
Beryllium Copper (Gold Plate)
INSULATORS : TEFLON

* OTHER SPECIFICATIONS
MARKING COLOR : BLACK

주파수별 * Port Insertion Loss 기입 할 것.

TOLERANCE	Decimal ±0.3	DATE	2022. 03. 03.	 RF & MICROWAVE TECHNOLOGY Tel : 82-32-347-8015 Fax : 82-32-347-8017
	Angle ±1°	APPROVED BY	S.L.SON	
MATERIAL	A6061 T6	CHECKED BY	S.L.SON	TITLE 4WAY POWER DIVIDER
		DRAWN BY	K.S.KIM	
FINISH	White Chromate	SCALE	1/1	A4 DWG NO. PD00650-7/1 REVISION 1 SHEET 1 of 1
		UNIT	mm	