


AD00020-7/2

D/CUT-7.4



SMA (J) SMA (J) BH
L:22.3mm(6-2.5-13.8)
BO/GO, PI/GO

AD00020-7/2

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40℃ ~ 125℃

S11/S22/S21(SWR, SWR, dB)

■_1GHz	- 1.00, 1.00, 0.01
■_3GHz	- 1.02, 1.01, 0.03
■_6GHz	- 1.03, 1.03, 0.04
■_8GHz	- 1.03, 1.03, 0.05
■10GHz	- 1.04, 1.03, 0.05
■12GHz	- 1.06, 1.05, 0.06
■14GHz	- 1.10, 1.10, 0.07
■16GHz	- 1.12, 1.12, 0.08
■18GHz	- 1.06, 1.07, 0.08
■MaX_	- 1.12, 1.12, 0.09

► NETWORK ANALYZER

► Test cable

► Test Adaptor


□ E5071B (~8.5GHz)

■ 2.4mm Male to 2.4mm Male


■ ZVA50 (~50GHz)

50GHz Cable

Trc1 S11 SWR 100 mU/ Ref1 U Cal



Trc3 S21 dB Mag 1 dB / Ref0 dB Cal



TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)