

AD00102-7/2

H/CUT-13.6



GASKET

N (J) N (J) BH
L:44.3mm(16.7-3-24.6)
BODY/SUCO PIN/Gold

AD00102-7/2

Frequency	
Insertion Loss	
VSWR	
Impedance	☒ 50Ω ☐ 75Ω
Temperature	-40°C ~ 125°C

S11/S22/S21(SWR, SWR, dB)

■_1.0GHz	- 1.03, 1.03, 0.00
■_2.0GHz	- 1.03, 1.03, 0.00
■_3.0GHz	- 1.06, 1.06, 0.00
■_4.0GHz	- 1.15, 1.15, 0.02
■_5.0GHz	- 1.13, 1.13, 0.00
■_6.0GHz	- 1.04, 1.08, 0.13
■_7.0GHz	- 1.08, 1.08, 0.03
■_8.0GHz	- 1.15, 1.11, 0.04

► NETWORK ANALYZER

► Test cable

► Test Adaptor

■ E5071B (~8.5GHz)

■ N Male to N Male

□ ZVA50 (~50GHz)

10GHz Cable (CF00539-7/1)

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

