

AD00158-7/1

AD00158-7/1

S11/S22/S21(SWR, SWR, dB)



SMA (P) SMB (J)  
ST L:19mm

BO/GO, PI/GO, CAP/GO

|                |               |
|----------------|---------------|
| Frequency      |               |
| Insertion Loss |               |
| VSWR           |               |
| Impedance      | ■ 50Ω □ 75Ω   |
| Temperature    | -40°C ~ 125°C |

|           |                    |
|-----------|--------------------|
| ■ _1.0GHz | - 1.03, 1.02, 0.08 |
| ■ _2.0GHz | - 1.08, 1.06, 0.13 |
| ■ _3.0GHz | - 1.09, 1.09, 0.15 |
| ■ _4.0GHz | - 1.09, 1.08, 0.16 |
| ■ _5.0GHz | - 1.07, 1.06, 0.17 |
| ■ _6.0GHz | - 1.11, 1.10, 0.19 |
| ■ _7.0GHz | - 1.17, 1.14, 0.23 |
| -----     |                    |
| ■ _8.0GHz | - 1.22, 1.23, 0.25 |

► NETWORK ANALYZER

► Test cable

► Test Adaptor

■ E5071B (~8.5GHz)

□ ZVA50 (~50GHz)

TR1 : IN PORT VSWR(S11), TR2 : OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

