


AD00344-7/4



QMA (J) SMA (J)  
ST L:19.8mm  
BO/SU, PI/GO

AD00344-7/4

|                |               |
|----------------|---------------|
| Frequency      |               |
| Insertion Loss |               |
| VSWR           |               |
| Impedance      | ■ 50Ω □ 75Ω   |
| Temperature    | -40°C ~ 125°C |

S11/S22/S21(SWR, SWR, dB)

|          |                    |
|----------|--------------------|
| ■_1.0GHz | - 1.07, 1.08, 0.28 |
| ■_2.0GHz | - 1.12, 1.13, 0.31 |
| ■_3.0GHz | - 1.08, 1.09, 0.34 |
| ■_4.0GHz | - 1.14, 1.14, 0.33 |
| -----    |                    |
| ■_5.0GHz | - 1.29, 1.28, 0.24 |
| ■_6.0GHz | - 1.53, 1.51, 0.05 |
| ■_7.0GHz | - 1.78, 1.83, 0.16 |
| ■_8.0GHz | - 1.88, 1.94, 0.22 |

► NETWORK ANALYZER ► Test cable

► Test Adaptor

■ E5071B (~8.5GHz)

□ ZVA50 (~50GHz)

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

