


* ELECTRICAL SPECIFICATIONS

1. Frequency Range : DC~20GHz
2. Impedance : 50Ω (Nominal)
3. V.S.W.R (MAX) : 1.2
4. Insertion Loss (MIN) : -0.7dB



■ MATING 검사 진행

SMP Female SMP Male

(Full detent) (Limited detent) (Smooth bore) (Catcher mit)

■ SMP Female ↔ Male KJ 제품Code


SMP Female	SMP Male (Full detent)	SMP Male (Limited detent)	SMP Male (Smooth bore)	SMP Male (Catcher mit)
CN03997	AD00722	CN03734	AD00715	-

■ Frequency range : DC ~ 40GHz

Engagement force	Full detent : ≤ 66.75N (=6.81kgf) Limited detent : ≤ 44.5N (4.54kgf) Smooth bore, Catchers mitt : ≤ 8.9N (=0.90kgf)
Disengagement force	Full detent : ≥ 22.25N (2.27kgf) Limited detent : ≥ 8.9N (=0.90kgf) Smooth bore, Catchers mitt : ≥ 2.2N (=0.22kgf)

REVISION				
REV	DESCRIPTION	DRAWN	APPR	DATE
IR	Initial Registration	S.H.KIM		2024.03.13.

3	INSULATOR	1	TEFLON		DAI02509-N/1
2	CONTACT	1	BeCu C17300	Gold Plate	DAC03419-5/1
1	BODY	1	BeCu C17300	Gold Plate	DAD00471-5/1
NO.	DESCRIPTION	Q'TY	MATERIAL	PLATING	CODE

TOLERANCE	Decimal ±0.2	DATE 2024. 03. 13.			 RF & MICROWAVE TECHNOLOGY Tel : 82-32-347-8015 Fax : 82-32-347-8017	
	Angle ±1°	APPROVED BY				
MATERIAL -		CHECKED BY			TITLE SMP50 (J) SMP50 (J) ST ADAPTOR	
		DRAWN BY S.H.KIM				
FINISH -		SCALE 8/1	UNIT mm		A4	DWG NO. AD00585-7/G
						REVISION I R