

CF00411-7/1



SMA-PS+SMA-PS
+RG178

SMA PS RG178

BO/GO, PI/GO, CH/BR/GO

CF00411-7/1 500mm

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40°C ~ 125°C

■_0.5GHz	- 1.04, 1.08, 0.54
■_1.0GHz	- 1.16, 1.16, 0.84
■_1.5GHz	- 1.27, 1.28, 1.09
■_2.0GHz	-
■_3.0GHz	- 1.68, 1.64, 1.83
■_4.0GHz	-
■_5.0GHz	- 2.70, 2.69, 3.37
■_6.0GHz	-

► NETWORK ANALYZER

► Test cable

► Test Adaptor

- ☐ E5071B (~8.5GHz)
- ☒ ZND (~8.5GHz)
- ☐ ZVA50 (~50GHz)

- ☒ N Male to SMA Male
10GHz Cable (CF00540-7/1)
- ☐ N Male to N Male
10GHz Cable (CF00539-7/1)
- ☐ 2.4mm Male to 2.4mm Male
50GHz Cable

TR1 : IN PORT VSWR(S11), TR2 : OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

