


CF00446-7/1



SMA JS+OPEN+47F

SMA JS 47F ↔ ◆8

BO/GO,PI/GO

CF00446-7/1

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40°C ~ 125°C

*1M - S11,S22,S21 (dB)

■ _1GHz/	1.03, 1.03, 0.32
■ _2GHz/	1.02, 1.03, 0.50
■ _3GHz/	1.12, 1.13, 0.62
■ _4GHz/	1.31, 1.30, 0.80
■ _5GHz/	1.32, 1.33, 0.90
■ _6GHz/	1.13, 1.16, 0.91
■ _7GHz/	1.18, 1.19, 1.01
■ _8GHz/	1.58, 1.59, 1.28
■ Max/	1.69, 1.74, 1.40

▶ NETWORK ANALYZER

▶ Test cable

▶ Test Adaptor

■ E5071B (~8.5GHz)

■ N Male to SMA Male

■ 2.92mm Female to 2.92mm Female

□ ZVA50 (~50GHz)

10GHz Cable (CF00540-7/1)

(KJ Code : AD00644-7/2_ / 2ea)

TR1 : IN PORT VSWR(S11), TR2 : OUT PORT VSWR(S22), TR3 : Insertion Loss (S21)

