

CF00548-7/3

VSWR:1.2@DC~10GHz



N-PS+SMA-PS
+141FJ(BLUE)

N PS (~10GHz)
BO/NI, PI/GO, CH/BR/NI
SMA PS (~27GHz)
BO/GO, PI/GO, CH/BR/NI

CF00548-7/3 1.5M	
Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40℃ ~ 125℃

1.5M - S11/S22/S21 (SWR, SWR, dB)		
■_2GHz	- 1.01, 1.02, 0.99	
■_4GHz	- 1.03, 1.04, 1.49	
■_6GHz	- 1.16, 1.07, 1.88	
■_8GHz	- 1.07, 1.07, 2.27	
■10GHz	- 1.14, 1.09, 2.58	
■12GHz	- 1.13, 1.08, 2.94	
■14GHz	- 1.07, 1.03, 3.23	
■16GHz	- 1.18, 1.06, 3.54	

■18GHz	- 1.14, 1.14, 3.82	

- ▶ NETWORK ANALYZER
- ▶ Test cable
- ▶ Test Adaptor
- ☐ E5071B (~8.5GHz)

☒ ZVA50 (~50GHz)
- ☒ 2.4mm Male to 2.4mm Male 50GHz Cable
- ☒ 2.92mm (J) to 2.92mm(J) AD00644-7/2

TR1 : IN PORT VSWR(S11), TR2 : OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

