

CF00956-7/1



SMBL-PL+SMBL-PL

+SIFS(BLACK)

SMBL PL SIFS V:16.3 CAPØ9

BO/NI, PI/GO, CC/BR/NI

CF00956-7/1 0.2M

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40°C ~ 125°C

0.2M - S11/S22/S21
(SWR, SWR, dB)

■_0.5GHz - 1.07, 1.06, 0.14
■_1.0GHz - 1.09, 1.09, 0.21
■_1.5GHz - 1.10, 1.10, 0.28
■_2.0GHz - 1.07, 1.07, 0.33
■_3.0GHz - 1.08, 1.08, 0.42

■_4.0GHz - 1.36, 1.34, 0.60
■_5.0GHz - 1.67, 1.65, 0.88
■_6.0GHz - 1.97, 1.99, 1.17

▶ NETWORK ANALYZER

▶ Test cable

▶ Test Adaptor

■ E5071B (~8.5GHz)

■ N Male to SMA Male

■ SMA (J) SMBL (J) ST

□ ZVA50 (~50GHz)

10GHz Cable (CF00540-7/1)

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

