

CF01105-7/1

PIMD



TNC-PS+TNC-PS

+141MF(BLUE)

TNC PS 141MF

BO/SU, PI/SI, CH/BR/NI

CF01105-7/1 300mm

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40°C ~ 125°C

300mm - S11/S22/S21 (SWR, SWR, dB)

■_1.0GHz	- 1.02, 1.02, 0.12
■_2.0GHz	- 1.09, 1.10, 0.20
■_3.0GHz	- 1.08, 1.08, 0.25
■_4.0GHz	- 1.17, 1.18, 0.30

■_5.0GHz	- 1.49, 1.49, 0.48
■_6.0GHz	- 1.66, 1.68, 0.65
■_7.0GHz	- 1.24, 1.25, 0.53
■_8.0GHz	- 1.55, 1.58, 0.89

► NETWORK ANALYZER

► Test cable

► Test Adaptor

■ E5071B (~8.5GHz)

■ N Male to SMA Male

■ SMA (J) TNC (J)

□ ZVA50 (~50GHz)

10GHz Cable (CF00540-7/1)

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

