

CF01107-7/1



4.3/10-PS(SCREW)+TNC-PS +EXLH-21R

4.3/10 (SCREW) PS EXLH-21R
BO/SU3 PI/SI5 CAP/NI
TNC PS EXLH-21R
BO/SU, PI/SI, CH/BR/NI

CF01107-7/1 640mm

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40°C ~ 125°C

640mm - S11/S22/S21 (SWR, SWR, dB)

■ _1.0GHz - 1.06, 1.07, 0.16
■ _2.0GHz - 1.08, 1.07, 0.24
■ _3.0GHz - 1.08, 1.07, 0.32
■ _4.0GHz - 1.27, 1.26, 0.41

■ _5.0GHz - 1.11, 1.08, 0.41
■ _6.0GHz - 1.30, 1.31, 0.54
■ _7.0GHz - 1.05, 1.06, 0.46
■ _8.0GHz - 1.12, 1.15, 0.58

► NETWORK ANALYZER

► Test cable

► Test Adaptor

■ E5071B (~8.5GHz)

■ N Male to N Male

■ 4.3/10 (J) N (J) AD00582-7/1

□ ZVA50 (~50GHz)

10GHz Cable (CF00539-7/1))

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

