

CF01341-7/1



SMA-PS+SMA-PS
+3D-FV(GRAY)

SMA PS

BO/Ni PI/Go HEX-CAP/BR/NI

CF01341-7/1 0.6M

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40°C ~ 125°C

0.6M - S11/S22/S21
(SWR, SWR, dB)

■ _0.5GHz	- 1.02, 1.00, 0.14
■ _1.0GHz	- 1.03, 1.04, 0.21
■ _1.5GHz	- 1.09, 1.09, 0.29
■ _2.0GHz	- 1.10, 1.11, 0.31
■ _3.0GHz	- 1.07, 1.08, 0.41
■ _4.0GHz	- 1.04, 1.04, 0.49
■ _5.0GHz	- 1.07, 1.05, 0.53

■ _6.0GHz	- 1.25, 1.23, 0.65

▶ NETWORK ANALYZER

▶ Test cable

▶ Test Adaptor

■ E5071B (~8.5GHz)

■ N Male to SMA Male

■ SMA (J) SMA (J) ST

□ ZVA50 (~50GHz)

10GHz Cable (CF00540-7/1)

AD00006-7/2

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

