



CF01386-7/1 2.5M	
Frequency	
Insertion Loss	
VSWR	
Impedance	☒ 50Ω ☐ 75Ω
Temperature	-40℃ ~ 125℃

2.5M - S11/S22/S21 (SWR,SWR,dB)		
☒ _0.5GHz	- 1.05, 1.04, 1.51	
☒ _1.0GHz	- 1.03, 1.03, 2.19	
☒ _1.5GHz	- 1.08, 1.07, 2.74	
☒ _2.0GHz	- 1.15, 1.12, 3.25	
☒ _3.0GHz	- 1.11, 1.13, 4.12	
☒ _4.0GHz	- 1.02, 1.20, 4.95	

☒ _5.0GHz	- 1.04, 1.23, 5.79	
☒ _6.0GHz	- 1.11, 1.15, 6.66	

- ▶ NETWORK ANALYZER
- ▶ Test cable
- ▶ Test Adaptor
- ☒ E5071B (~8.5GHz)

☒ N Male to SMA Male

☐ ZVA50 (~50GHz)
- 10GHz Cable (CF00540-7/1)

N (J) SMA (J) AD00424-7/1

SMA (J) SMBL (P) ST AD00491-7/4

TR1 : IN PORT VSWR(S11), TR2 : OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

