

CF01404-7/1

CF01404-7/1 0.5M

0.5M - S11/S22/S21
(SWR, SWR, dB)

D/CUT-5.9 BHL: 16mm



SMA-JB+SMA-PS
+85FJ(CLEAR)



SMA JB 8HD BH: 16mm

BO/Ni PI/Go

SMA PS

BO/Go PI/Go CAP/NI

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40°C ~ 125°C

■_1.0GHz	- 1.00, 1.01, 0.37
■_2.0GHz	- 1.06, 1.07, 0.57
■_3.0GHz	- 1.09, 1.07, 0.72
■_4.0GHz	- 1.06, 1.05, 0.86
■_5.0GHz	- 1.17, 1.13, 0.99
■_6.0GHz	- 1.13, 1.11, 1.11
■_7.0GHz	- 1.17, 1.15, 1.22
■_8.0GHz	- 1.36, 1.36, 1.43

► NETWORK ANALYZER

► Test cable

► Test Adaptor

■ E5071B (~8.5GHz)

■ N Male to SMA Male

■ SMA (J) SMA (J) ST

□ ZVA50 (~50GHz)

10GHz Cable (CF00540-7/1)

AD00006-7/2

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

