


REVISION		
REV	DESCRIPTION	DATE
1	CHANGED SILK PRINT	2004.10.19.



* ELECTRICAL SPECIFICATIONS
 Frequency Range : 824.0 ~ 849.0MHz
 Coupling Value : 10dB $\pm$ 0.75dB
 Coupling Flatness : $\pm$ 0.15dB
 Insertion Loss (Max.) : 0.66dB
 V.S.W.R (Max.) : 1.2 : 1
 Directivity (Min.) : 20.0dB
 Power Handling (Max.) : 1.0W
 Impedance : 50 Ω

* MECHANICAL SPECIFICATIONS
 HOUSING : A6061 T6 (White Chromate)
 CONNECTORS : MBsBD (Gold Plate)
 CONNECTORS PINS : Beryllium Copper (Gold Plate)
 INSULATORS : TEFLON

REVISION		REV.A	NO.	DESCRIPTION		Q'TY	MATERIAL	PLATING	REMARKS
TOLERANCE	Decimal	DATE		2004. 10. 19.		 RF & MICROWAVE TECHNOLOGY 1d : 82-32-347-8015 Fax : 82-32-347-8017 KJ COMTECH CO.,LTD.			
	± 0.3	APPROVED BY							
	Angle	CHECKED BY							
MATERIAL		DRAWN BY				TITLE			
A6061 T6						10dB Directional Coupler			
FINISH		SCALE	UNIT			A4	DWG NO.	DC00003-7/1	
White Chromate		1/1	mm				SHEET	1	OF