



REVISION				
REV	DESCRIPTION	DRAWN	APPR	DATE
IR	Initial Registration	K.I.CHO	J.H.YOUN	2005.09.08.
A	업체요구에 의한 BAR CODE 추가(설번200810-0030)	K.I.CHO	J.H.YOUN	2008.10.31.
B	도금변경(황색크로메이트->백색크로메이트)	K.I.CHO	J.H.YOUN	2011.06.10.



* ELECTRICAL SPECIFICATIONS
Frequency Range : 800.0~900.0MHz
Insertion Loss (Max.) : 3.3dB
V.S.W.R (Max.) : 1.2 : 1
Isolation (Min.) : 20.0dB
Power Handling (Max.) : 1.0W
Impedance : 50.0Ω

* MECHANICAL SPECIFICATIONS
HOUSING : A6061 T6 (White Chromate)
CONNECTORS : MBsBD (Nickel Plate)
CONNECTORS PINS : Beryllium Copper (Gold Plate)
INSULATORS : TEFLON

TOLERANCE	Decimal	DATE 2011. 06. 10.		 RF & MICROWAVE TECHNOLOGY Tel : 82-32-347-8015 Fax : 82-32-347-8017
	Angle	APPROVED BY	J.H.YOUN	
MATERIAL	±1°	CHECKED BY		KJ COMTECH CO.,LTD. TITLE 2 WAY POWER DIVIDER
	A6061 T6	DRAWN BY	K.I.CHO	
FINISH	White Chromate	SCALE	1/1	A4 DWG NO. PD00023-7/3 REVISION B SHEET 1 of 1
		UNIT	mm	