



REVISION				
REV	DESCRIPTION	DRAWN	APPR	DATE
1	Initial Registration	S.L.SON	J.H.YOUN	2013.06.19.



* ELECTRICAL SPECIFICATIONS
Frequency Range : 80.0 ~ 110.0MHz
Insertion Loss (Max.) : 7.02dB
V.S.W.R (Max.) : 1.2 : 1
Isolation (Min.) : 20.0dB
Power Handling (Max.) : 1.0W
Impedance : 50.0Ω

* MECHANICAL SPECIFICATIONS
HOUSING : A6061 T6 (White Chromate)
CONNECTORS : MBsBD (Nickel Plate)
CONNECTORS PINS : Beryllium Copper (Gold Plate)
INSULATORS : TEFLON

* OTHER SPECIFICATIONS
MARKING COLOR : BLACK

TOLERANCE	Decimal ±0.3	DATE 2013. 6. 19.		 RF & MICROWAVE TECHNOLOGY Tel : 82-32-347-8015 Fax : 82-32-347-8017
	Angle ±1°	APPROVED BY	J.H.YOUN	
MATERIAL	A6061 T6	CHECKED BY	J.H.YOUN	KJ COMTECH CO.,LTD. TITLE 4WAY POWER DIVIDER
		DRAWN BY	S.L.SON	
FINISH White Chromate	SCALE 1/1	UNIT mm		A4 DWG NO. PD00490-7/1 REVISION 1 SHEET 1 of 1