

SMA TERMINATION

15.5±0.3

ø7.8

55.0±10mm

ø3.0

5

REVISION

REV	DESCRIPTION	DRAWN	APPR	DATE
1	Initial Registration	I.C.KIM	I.C.KIM	2014.01.07.
5	연결홀이 변경 ø6.35 => ø3.0	T.J.KIM	J.H.YOUN	2016.01.22.

ELECTRICAL DATA

1	IMPEDANCE : 50Ω
2	FREQUENCY : DC~ 6GHz
3	V.S.W.R : 1.2 : 1 (MAX)
4	POWER : 1/8 Watt

MATERIALS

1	BODY,CHAIN : BRASS / Nickel Plated
2	CONTACT : BRASS / Gold Plated
3	INSULATOR : PTFE
4	CAP : BRASS / Nickel Plated

주 기

1. 염수 96시간 이상에서 이상이 없을 것
- 염수처리 할 것.

NO.	DESCRIPTION	Q'TY	MATERIAL	PLATING	CODE
DATE	2016. 01. 22.		 KJ COMTECH CO.,LTD. RF & MICROWAVE TECHNOLOGY Tel : 82-32-347-8015 Fax : 82-32-347-8017		
TOLERANCE	Decimal ±0.1 Angle ±1°	APPROVED BY J.H.YOUN			
MATERIAL	-	CHECKED BY S.L.SON	TITLE SMA50 (P) TERM 1W		
FINISH	-	DRAWN BY T.J.KIM			
SCALE	3/1	UNIT mm	A4	DWG NO. TM00139-N/5	
				REVISION 5	SHEET 1 of 1